

Lithium ion Polymer (LP) Battery Individual Data Sheets

LP-563569 have a combination of high energy density, super light and ultra thin. It's a perfect power source solution for mobile phone , small PDAs and other handheld device..

Specifications

Nominal voltage	3.7V	Cut-off voltage	3.0V
Standard charge method	Charging the cell initially with constant current at 0.5C and then with constant voltage at 4.2V till charge current <0.05C		
Max. charge current	1C	Max. discharge current	1.5C
Standard charge	0.5C×5hrs	Rapid charge	1C ×2.5hrs
Operating temperature		℃	°F
	Charging	0℃ ~ 45℃	32°F ~ 113°F
	Discharging	-20℃ ~ 60℃	-4°F ~ 140°F
	Storage	-20℃ ~ 45℃	-4°F ~ 113°F
Cycle Life	≥500 Cycles (@0.5C discharge, 23℃)	Self-discharge	Residual capacity>90% (@25℃±2℃, 30 days)

Remark:

*1 @ 0.2C discharge, 23℃

*2 Impedance is measured at AC 1KHz after Standard Charge.

*3 Cell weight is the approximate value for reference.

Cell Dimension

	mm	inch
Length	69.0 ± 0.5	2.71 ± 0.02
Width	34.5 ± 0.5	1.36 ± 0.02
Thickness	Max. 5.80	Max. 0.23

